



Rohr-Mauerdurchführung ERV-1 **ERV-1**

Nennweite DN mm	Gewicht ca. kg	passend für äußeren Rohr - Ø		lichter Mauerrohr - Ø B mm	Mauer- flansch - Ø D mm	Vorbaulänge A ca. mm	Klemm- ring - Ø DF mm
		DIN Da mm	ISO Da mm				
40	10	44,5	48,3	87,8	195	40	435
50	11,5	57	60,3	100,8	210	40	450
65	13	76	76,1	113	225	40	460
80	14,5	89	88,9	131,7	240	40	480
100	18	108	114,3	159,3	265	40	510
125	23	133	139,7	182,9	300	40	535
150	26	159	168,3	207,3	325	40	560
175	29	191	193,7	231,9	350	40	585
200	32	216	219,1	260,4	375	40	615
250	37	267	273	317	430	45	665
300	45	318	323,9	367	485	45	715
350	54	368	355,6	415	535	45	765
400	63	419	406,4	470	590	45	820
450	69	470	457,2	520	640	45	870
500	76	521	508	570	690	45	920
550	82	572	558,8	620	740	45	970
600	105	622	609,6	670	810	55	1020
650	113	670	660,4	720	860	55	1070
700	120	720	711,2	770	910	55	1120
800	148	820	812,8	873	1015	55	1225
900	164	920	914,4	973	1115	55	1325
1000	179	1020	1016	1073	1215	55	1425
1100	216	1120		1174	1320	55	1530
1200	288	1220		1274	1435	60	1630
1300	321	1320		1374	1540	60	1730
1400	338	1420		1474	1640	60	1830
1500	369	1520		1574	1740	60	1930
1600	412	1620		1675	1840	60	2035
1800	571	1820		1876	2075	80	2235
2000	673	2020		2080	2260	80	2440

Gewicht für Wanddicke W = 300 mm