













# R<sub>2</sub>

## Reduzierstück R<sub>2</sub> PN 25

Nennweite		Gewicht ca. kg	Ausführung	Baulänge mm	Gesamtlänge mm	größter Durchmesser D mm
DN <sub>1</sub> mm	DN <sub>2</sub> mm					
350	450	144	B	65	85	680
350	500	180	B	65	120	730
350	600	260	B	65	190	845
350	700	352	B	65	260	960
400	450	137	A	70		680
400	500	177	A	70		730
400	600	244	B	65	150	845
400	700	335	B	65	220	960
400	800	447	B	65	300	1085
450	500	188	A	84		730
450	600	145	B	65	120	845
450	700	317	B	65	190	960
450	800	429	B	65	260	1085
500	600	204	A	65		845
500	700	296	B	65	160	960
500	800	440	B	70	220	1085
500	900	547	B	70	300	1185
600	700	281	A	74		960
600	800	410	B	74	150	1085
600	900	523	B	74	220	1185
600	1000	693	B	74	300	1320
700	800	344	B	55	85	1085
700	900	459	B	55	150	1185
700	1000	628	B	55	220	1320
750	800	558	A	134		1085
750	900	479	B	65	120	1185
750	1000	671	B	65	190	1320